

## Powerful LED Panel also for Mobile Use

- High light output with 400 W continuously adjustable
- Variable colour temperature between 2,700 and 6,500 K
- 5 light effects, each with a frequency of 1 - 10
- Power supply from mains or rechargeable batteries (batteries not included)
- Ideal for use in the studio and on the road
- High colour accuracy for photographers and filmmakers (CRI > 97, TLCI > 98)
- Illuminance of 8,850 lx at 1 m
- Flicker-free light characteristic is ideal for video recordings
- Included barndoors direct the light in the desired direction
- Can be remotely controlled with separately available TR-Q7 or EF-RC radio remote controls or conveniently via app



### Technical Data

<b>Power</b>	400 W
<b>Color temperature</b>	2,700 – 6,500 K in 100 K steps
<b>Color rendering index (CRI)   Television Lighting Consistency Index (TLCI)</b>	> 97   > 98
<b>Power adjustment</b>	1 - 100 % in 1 % or 10 % steps
<b>Illuminance</b>	1m: > 6,500 lx (2,700 K)   > 8,850 lx (5,000 K)   > 7,500 lx (6,000 K)
<b>Light effects</b>	TV   Flickering Bulb   Fireworks   Thunderstorm mode   Blink mode - each has a frequency of 1 to 10
<b>Bowens S-type mount</b>	No
<b>Channels   Groups</b>	32 (00 - 31)   16 (A - J / L / O / P / Q / S / U)
<b>Remote control</b>	Integrated, 2.4 GHz   Compatible to TR-Q7 / EF-RC
<b>Bluetooth®* version</b>	4.2
<b>Radio frequency band (GHz)</b>	2.402-2.480 GHz
<b>Transmission power maximum</b>	6 dBm
<b>Battery operation</b>	Battery operation possible with: 1 V-mount battery (max. 75 % power): 14.4 V / 10 A   14.8 V / 10 A   1 V-mount battery (max. 100 % power): 26 V / 8.5 A   28.8 V / 29.6 V / 7.5 A   2 V-mount batteries (max. 100 % power): 14.4 V / 10 A   14.8 V / 10 A   26 V / 8.5 A   28.8 V / 29.6 V / 7.5 A   V-mount batteries not included. Input: 14.4 – 33.6 V max. 10 A   ≥ 190 Wh
<b>Power supply</b>	95 – 245 V, 50 / 60 Hz, Input: max. 1.5 A
<b>Volume cooling fan</b>	< 30 dB, Fan can be switched off at a max. output of 80%
<b>Additional features</b>	LC display   Tripod mount (5/8")   U-bracket mount 16 mm / 28 mm   Barn doors   Carrying handle   Lighting angle 120°   DMX 512 control   App "Jinbei (Studio)", range > 15 m
<b>Dimensions   Weight</b>	80 x 52 x 11 cm   11 kg

### What's in the Box and Packaging Details

<b>What's in the box</b>	EFP-400 Bi-Color V2, barn doors, U-bracket, mains cable, user manual
<b>Packaging dimensions   Weight</b>	84 x 62 x 23 cm   15.2 kg

Specifications are subject to change without notice. \*The Bluetooth® word mark and logos are registered trademarks of the Bluetooth SIG, Inc. and any use of such marks by Rollei is under license. Other trademarks and trade names are the property of their respective owners. \*Not included in delivery.

Article no.: 2344

