

EF-120Bi – Compact Continuous Light For Bi-color Illumination

- 120 Watt power: Bright illumination for professional shots
- Bi-color adjustment: Variable color temperature from 2,700 to 6,500 Kelvin for versatile lighting design
- Battery operation with adapter (optional): Flexible power supply for outdoor use
- App control: Convenient adjustment of lighting via smartphone
- Bowens connector: Compatibility with a wide range of light shapers and accessories



Technical Data

Number of LEDs	1
Power	120.0 W
Energy efficiency class (EU 2017/1369)	G
EU energy efficiency class spectrum (EU 2017/1369)	A – G
Color temperature	2,700 – 6,500 K
Color rendering index (CRI) Television Lighting Consistency Index (TLCI)	96 97
Power adjustment	Infinitely adjustable in 1%-steps
Illuminance	3,200 K: 18,400 lux (0.5 m), 5,080 lux (1 m), 2,320 lux (1.5 m); 4,500 K: 20,300 lux (0.5 m), 5,610 lux (1 m), 2,550 lux (1.5 m); 5,500 K: 21,500 lux (0.5 m), 5,880 lux (1 m), 2,710 lux (1.5 m)
Light effects	9
Bowens S-Type mount	Yes
Remote control	App
Bluetooth®* version	5.0
Radio frequency band	2.4 GHz
Transmission power maximum	6 dBm
Battery operation Battery running time	With separately available adapters reduced power to 100.0 W, battery life of > 100 min.
Power supply	Input: AC 100 – 240 V, 50/60 Hz, max. 4.0 A Output: DC 24 V – 5.5 A, 144.0 W
Rated input power	144.0 W
Volume cooling fan	< 30 db
Dimensions (L x W x H) Weight	20.8 x 12.2 x 16.5 cm 940 g

What's in the Box and Packaging Details

What's in the box	EF-120Bi, reflector, protective cap, diffuser fabric, power cord, quick start guide
Packaging dimensions (L x W x H) Weight	32 x 21 x 22 cm 1.0 kg

Specifications are subject to change without notice. *The Bluetooth® word mark and logos are registered trademarks of the Bluetooth SIG, Inc. and any use of such marks by Rollei is under license. Other trademarks and trade names are the property of their respective owners. *Not included in delivery.

Item No.: 2482

