

## Bi-colored LED Continuous Light with 170 W Power

- Constant, powerful LED Continuous Light
- Color temperature adjustable between 2,700 K and 6,500 K
- 10 light effects, operation via app or separate remote control (not included)
- Optional power supply via rechargeable battery (not included)



### Technical Data

<b>Number of LEDs</b>	1
<b>Power</b>	170 W
<b>Energy efficiency class (EU 2017/1369)</b>	F
<b>EU energy efficiency class spectrum (EU 2017/1369)</b>	A – G
<b>Color temperature</b>	2,700 K – 6,500 K
<b>Color rendering index (CRI)   Television Lighting Consistency Index (TLCI)</b>	97   98
<b>Power adjustment</b>	0 – 100% in 1 % steps
<b>Illuminance</b>	lux measurements 3,200 K, measured at 0.5 m / 1 m / 1.5 m: 18,200 / 4,660 / 2,140 lx lux measurements 4,500 K, measured at 0.5 m / 1 m / 1.5 m: 22,900 / 5,800 / 2,660 lx lux measurements: 5,500 K, measured at 0.5 m / 1 m / 1.5 m 18,500 / 4,650 / 2,150 lx
<b>Light effects</b>	10
<b>Bowens S-type mount</b>	Yes
<b>Channels   Groups</b>	32   16
<b>Remote control</b>	Via remote control (not included) or app
<b>Bluetooth®* version</b>	4.2
<b>Radio frequency band</b>	2.402 – 2.480 GHz
<b>Transmission power maximum</b>	6 dBm
<b>Battery operation</b>	Optionally via V-mount battery adapter, not included in scope of delivery
<b>Power supply</b>	AC 100 – 240 V   50 / 60 Hz
<b>Volume cooling fan</b>	Max. 30 dB.
<b>Connections</b>	Spigot connector, shield mount, Bowens S-type-mount
<b>Dimensions (L x W x H)   Weight</b>	26.5 x 13.5 x 23 cm   2.2 kg

### What's in the Box and Packaging Details

<b>What's in the box</b>	EF-150Bi, EF boost reflector 70°, protective cap, power cable (4.5 m), user manual
<b>Packaging dimensions   Weight</b>	48.5 x 27.5 x 22.0 cm   3.45 kg

Specifications are subject to change without notice. \*The Bluetooth® word mark and logos are registered trademarks of the Bluetooth SIG, Inc. and any use of such marks by Rollei is under license. Other trademarks and trade names are the property of their respective owners.