

The JINBEI LED permanent light for every use.

- 160 Watts light output for professional results in any scenario
- Color temperature choosable between 2,700- 6,500K
- Color rendering index of 97 and TLCI of 98
- Active fan cooling



Technical Data

Number of LEDs	1, COB-LED
Power	Input: 192 Watt Output: 160 Watt
Energy efficiency class (EU 2017/1369)	G
EU energy efficiency class spectrum (EU 2017/1369)	A – G
Color temperature	2,700 - 6,500K
Color rendering index (CRI) Television Lighting Consistency Index (TLCI)	97 98
TLMF	TM-30Rf=93, TM-30Rg=100
SSI	75
CQS	95.9
Flicker-free up to x FPS	Flicker-free up to 20.000 frames per second
DMX	No
Power adjustment	0-100%, in 1%-Steps
Illuminance	3,200 K: 20,500 lx (0.5m), 4,990 lx (1m), 2,290 lx(1.5m) 4,500 K: 27,300 lx (0.5m), 6,680 lx (1m), 3,100 lx(1.5m) 5,500 K: 23,500 lx (0.5m), 5,700 lx (1m), 2,680 lx(1.5m) (measured without reflector)
Light effects	10
Bowens S-type mount	Yes
Channels Groups	32 16
Remote control	2,4 GHz, Bluetooth (App)
Bluetooth®* version	5.0
Radio frequency band	2.402-2.482
Transmission power maximum	6 dBm
Battery operation Battery running time	No Battery operation
Power supply	Input: AC 100 - 240 V; 50/60 Hz
Volume cooling fan	<30db
Connections	Light stand connection, Bowens S-Type connection
Dimensions (L x W x H) Weight	26.5 x 23 x 13.5 cm 2.2 kg

What's in the Box and Packaging Details

What's in the box	EF-160Bi LED light, EF-Boost-Reflector, protective cap, 4.5 meters power cable
Packaging dimensions (L x W x H) Weight	48.5 x 27.5 x 22 cm 3.45 kg

Specifications are subject to change without notice. *The Bluetooth® word mark and logos are registered trademarks of the Bluetooth SIG, Inc. and any use of such marks by Rollei is under license. Other trademarks and trade names are the property of their respective owners. *Not included in delivery.

Item No.: 1114



6 933793 930213