

The JINBEI LED Continuous Light.

- 300 Watts light output for professional results in any scenario
- Perfectly suitable for filmmakers and videographers, CRI of 96 and TLCI of 97
- Color temperature of daylight-like 5,500K



Technical Data

Number of LEDs	1, COB-LED
Power	Input 360W, Output 300W
Energy efficiency class (EU 2017/1369)	F
EU energy efficiency class spectrum (EU 2017/1369)	A – G
Color temperature	5,500K
Color rendering index (CRI) Television Lighting Consistency Index (TLCI)	96 98
TLMF	TM-30 Rf=94, TM-30Rg=102
SSI	74
CQS	96.5
DMX	No
Flicker-free up to x FPS	Up to x FPS 20,786
Power adjustment	0-100%, in 1%-steps
Illuminance without reflector	5500K : 45,400 lx (0,5m) / 12,900 lx (1m) / 5,720 lx(1,5m)
Light effects	9
Bowens S-type mount	Yes
Channels Groups	32 16
Remote control	Yes
Bluetooth®* version	5.0
Radio frequency band	2,4 GHz
Transmission power maximum	6 dBm
Battery operation Battery running time	No battery operation
Power supply	Input: AC 100 - 240 V; 50/60 Hz; 360,0 W
Volume cooling fan	<30db, measured on 30 cm
Connections	Light stand connection, Bowens S type connection
Dimensions (L x W x H) Weight	34.5 x 21.5 x 32.5 cm 3.65 kg

What's in the Box and Packaging Details

What's in the box	EL-300 LED light, protective cap, 4.5 meters power cable, manual
Packaging dimensions (L x W x H) Weight	44.0 x 26.0 x 24.0 cm 4.8 kg

Specifications are subject to change without notice. *The Bluetooth® word mark and logos are registered trademarks of the Bluetooth SIG, Inc. and any use of such marks by Rollei is under license. Other trademarks and trade names are the property of their respective owners. *Not included in delivery.