

The JINBEI Bi LED Continuous Light.

- 300 Watts Bi LED light output for professional results in any scenario
- Perfectly suitable for filmmakers and videographers, CRI of 96 and TLCI of 98
- Color temperature variably adjustable between 2,700-6,500K



Technical Data

Number of LEDs	1, COB-LED
Power	Input 360W, Output 300W
Energy efficiency class (EU 2017/1369)	F
EU energy efficiency class spectrum (EU 2017/1369)	A – G
Color temperature	2,700 – 6,500 K
Color rendering index (CRI) Television Lighting Consistency Index (TLCI)	96 98
TLMF	TM-30 Rf=94, TM-30Rg=102
SSI	75
CQS	95
DMX	No
Flicker-free up to x FPS	Up to x FPS 21,471
Power adjustment	0-100%, in 1%-steps
Illuminance without reflector	3,200K 0,5 m 37.600 lux; 1,0 m 9.180 lux; 1,5 m 4.430lux
	4,500K 0,5 m 50.900 lux; 1,0 m 11.700 lux; 1,5 m 5.930 lux
	5,500K 0,5 m 43.300 lux; 1,0 m 10.100 lux; 1,5m 5.160 lux
Light effects	9
Bowens S-type mount	Yes
Channels Groups	32 16
Remote control	Yes
Bluetooth®* version	5.0
Radio frequency band	2,4 GHz
Transmission power maximum	6 dBm
Battery operation Battery running time	No battery operation
Power supply	Input: AC 100 - 240 V; 50/60 Hz; 360,0 W
Volume cooling fan	<30db, measured on 30 cm
Connections	Light stand connection, Bowens S type connection
Dimensions (L x W x H) Weight	34.5 x 21.5 x 32.5 cm 3.65 kg

What's in the Box and Packaging Details

What's in the box	EL-300Bi LED light, protective cap, 4.5 meters power cable, manual
Packaging dimensions (L x W x H) Weight	44.0 x 26.0 x 24.0 cm 4.8 kg

Specifications are subject to change without notice. *The Bluetooth® word mark and logos are registered trademarks of the Bluetooth SIG, Inc. and any use of such marks by Rollei is under license. Other trademarks and trade names are the property of their respective owners. *Not included in delivery.

