



LED Continuous Light with 300 W Power

- Constant, powerful LED continuous light
- Daylight-like color temperature 5,500 K
- 16 light effects, operation via app or separate remote control (not included)
- Optional power supply via rechargeable battery (not included)



Technical Data

Number of LEDs	1
Power	325 W
Energy efficiency class (EU 2017/1369)	F
EU energy efficiency class spectrum (EU 2017/1369)	A – G
Color temperature	5,500 K
Color rendering index (CRI) Television Lighting Consistency Index (TLCI)	97 98
Power adjustment	0 – 100 % in 1 % steps
Illuminance	49,000 / 12,100 / 5,560 lx, measured at 0.5 m at 5,500 K
Light effects	15
Bowens S-type mount	Yes
Channels Groups	32 16 groups
Remote control	Via remote control (not included) or app
Bluetooth®* version	4.2
Radio frequency band	2.402 – 2.480 GHz
Transmission power maximum	6 dBm
Battery operation	Optionally via V-mount battery adapter, not included in scope of delivery
Power supply	Input EFII-300: DC 48 V = 7.5 A; 360 W Input power supply: AC 100 – 240 V; 50 / 60 Hz Output power supply: DC 48 V = 7.5 A; 360 W
Volume cooling fan	Max. 30 dB
Connections	Bowens S-type mount, umbrella mount, tripod mount, carrying handle, U-bracket
Additional features	DMX, LC display, integrated radio receiver, 2.4 GHz, range > 100 m beam angle > 120°
Dimensions Weight	31.5 x 22.5 x 35 cm 3.5 kg

What's in the Box and Packaging Details

What's in the box	EFII-300, EF boost reflector 70°, protective cap, power supply mount with tripod clamp, power supply, power cable for power supply, manual
Packaging dimensions Weight	55 x 24.0 x 25.0 cm 5.91 kg

Specifications are subject to change without notice. *The Bluetooth® word mark and logos are registered trademarks of the Bluetooth SIG, Inc. and any use of such marks by Rollei is under license. Other trademarks and trade names are the property of their respective owners.

