

EF-80Bi - Compact Continuous Light For Bi-color Illumination

- 80 Watt power: Bright illumination for professional shots
- Bi-color adjustment: Variable color temperature from 2,700 to 6,500 Kelvin for versatile lighting design
- Battery operation with adapter (optional): Flexible power supply for outdoor use
- · App control: Convenient adjustment of lighting via smartphone

 Bowens connector: Compatibility with a wide range of light shapers and accessories



Technical Data	
Number of LEDs	1
Power	80.0 W
Energy efficiency class (EU 2017/1369)	G
EU energy efficiency class spectrum (EU 2017/1369)	A – G
Color temperature	2,700 – 6,500 K
Color rendering index (CRI) Television Lighting Consistency Index (TLCI)	96 97
Power adjustment	Infinitely adjustable in 1-%-steps
Illuminance	3,200 K: 16,100 lux (0.5 m), 3,700 lux (1 m), 1,690 lux (1.5 m); 4,500 K: 17,800 lux (0.5 m), 4,060 lux (1 m), 1,850 lux (1.5 m), 5,500 K: 18,700 lux (0.5 m), 4,250 lux (1 m), 1,950 lux (1.5 m)
Light effects	9
Bowens S-Type mount	Yes
Remote control	Арр
Bluetooth®* version	5.0
Radio frequency band	2.4 GHz
Transmission power maximum	6 dBm
Battery operation Battery running time	With separately available adapters reduced power to 60.0 W, battery life of > 80 min.
Power supply	Input: AC 100 – 240 V, 50/60 Hz, max. 4.0 A Output: DC 24 V – 4.0 A, 96.0 W
Rated input power	96.0 W
Volume cooling fan	< 30 db
Dimensions (L x W x H) Weight	20.8 x 12.2 x 16.5 cm 940 g

What's in the Box and Packaging Details	
What's in the box	EF-80Bi, reflector, protective cap, diffuser fabric, power cord, quick start guide
Packaging dimensions (L x W x H) Weight	32 x 21 x 22 cm 1.0 kg

Specifications are subject to change without notice. *The Bluetooth® word mark and logos are registered trademarks of the Bluetooth SIG, Inc. and any use of such marks by Rollei is under license. Other trademarks and trade names are the property of their respective owners. *Not included in delivery.

6 933793 930879