


## **EFD-60Bi Bi-Color LED Light**

## Compact and Flexible Bi-Color Permanent Light, Ideal for Videos on Location

- 60 W power, infinitely variable
- Variable colour temperature between 2,700 and 6,500 K
- CRI colour rendering index at over 97 and TLCI at over 98
- 9 different light effects
- Constant brightness mode independent of colour temperature
- Angle and height adjustable
- Battery operation possible via separately available battery adapter with handle for 2x NP-F970 batteries (not included)
- Lightweighted with 660 g
- 2,600 lx at 1 m without reflector at 5,500 K
- App operation "Jinbei (Studio)"



EFD-60

Technical Data	
Power	60 W
Color temperature	2,700 – 6,500 K
Color rendering index (CRI)   Television Lighting Consistency Index (TLCI)	>97   >98
Power adjustment	0 - 100 % in 1 % or 10 % steps
Illuminance	2,600 lx (1 m, 5,500 K, without reflector)
Light effects	FX0: Constant Brightness Mode FX1: TV FX2: Broken Bulb FX3: Storm FX4: Flame FX5: Breathing FX6: Paparazzi FX7: High/Low light FX8: SOS FX9: Warning light
Bowens S-type mount	No, here: Jinbei mount
Remote control	App operation "Jinbei (Studio)", range > 15 m
Bluetooth®* version	4.2
Radio frequency band (GHz)	2.402-2.480 GHz
Transmission power maximum (dBm)	6 dBm
Battery operation	Via separately available battery adapter with handle for 2x NP-F970 batteries (not included)
Power supply	AC 100 - 240 V / 50/60 Hz / Fuse 2.5 A
Volume cooling fan	< 35 dB
Connections	Jinbei mount for light shapers   Tripod thread
Additional features	Display   Angle and height adjustable
Dimensions   Weight	16 x 12.2 x 8.1 cm   0.66 kg

## Lieferumfang und Verpackungsdetails Lieferumfang

EFD-60Bi, EFD-60 reflector, protective cap, power supply, power supply bag, carrying bag, manual 41 x 23 x 23 cm | 2.665 kg

Specifications are subject to change without notice. \*The Bluetooth® word mark and logos are registered trademarks of the Bluetooth SIG, Inc. and any use of such marks by Rollei is under license. Other trademarks and trade names are the property of their respective owners. \*Not included in delivery.



## www.jinbei-deutschland.de/en

Verpackungsmaße | -Gewicht