

P80RGB LED Panel – Powerful Panel With Triple Brightness

- 80 watt power: Infinitely adjustable
- 900 LEDs: In cool white, warm white and RGB colors for uniform illumination
- Triple brightness: Through special lens technology
- Variable Color Temperature: Adjustable from 2,000 to 7,500 K
- Dual power supply: Battery use possible, perfect for on the go



Technical Data

Number of LEDs	900 LEDs (360 cool white, 360 warm white and 180 RGB LEDs)
Power	80.0 W
EU energy efficiency class (EU 2017/1369)	G
EU energy efficiency class spectrum (EU 2017/1369)	A – G
Color temperature	2,700 – 7,500 K
Hues	0 – 359°
Color rendering index (CRI)	> 96
Power adjustment	0 – 100 %
Illuminance in CCT mode without light shaper at 0.5 m	33,000 lx (2,700 K) 36,000 lx (5,500 K) 36,000 lx (7,500 K)
Illuminance in CCT mode with light shaper at 0.5 m	14,000 lx (2,700 K) 15,000 lx (5,500 K) 15,000 lx (7,500 K)
Illuminance in HSI mode with diffuser at 1.0 m	800 lx (red) 1,400 lx (green) 250 lx (blue) 400 lx (yellow) 500 lx (cyan) 240 lx (magenta)
Light effects	26
Bowens S-type mount	No
Remote control	2.4 GHz
Battery operation Battery running time	2 NP-F batteries > 60 min (2x NP-F 970)
Power supply	DC 12.0 – 24.0 V, max. 4.0 A
Additional features	Display, tripod mount, barndoors, diffuser, illumination angle 120°, App operation via the "Jinbei (Studio) App"
Dimensions (L x W x H) Weight	43.5 x 35.7 x 5.8 cm 3.34 kg

What's in the Box and Packaging Details

What's in the box	1x P80RGB LED panel, 1x barndoors, 1x AC adapter
Packaging dimensions (L x W x H) Weight	49.2 x 40.2 x 11.2 cm 5.05 kg

Specifications are subject to change without notice. *The Bluetooth® word mark and logos are registered trademarks of the Bluetooth SIG, Inc. and any use of such marks by Rollei is under license. Other trademarks and trade names are the property of their respective owners. *Not included in delivery.

Item No.: 1159

